



ADVANCED ADHESION INC.

MARKET-READY ADHESIVE FORMULATIONS

Mr. Sticky's® Tentacle Glue® - Sales Points

Welcome to the sales team for Mr. Sticky's® Tentacle Glue®! In order to assist your sales effort, we have compiled the following Features and Benefits that may help your customers understand the product. Please feel free to offer us any comments and or successful sales points so that we can add them to this document.

Most buyers want to know what is different about this adhesive versus existing glues:

No-Clamp Glue Joints: Bond odd-angled or curved joints with ease using no clamps! Prepare a loose fitting spline, or standard butt joint. Apply glue into the joint, assemble with spline or push together butt-joint. Secure with duct tape. Remove tape when adhesive is cured! *NOTE: Traditional wood glues cannot bond loose fitting joints.*

Flexible Toughness: Wood expands and contracts in response to changes in humidity and temperature. Tentacle Glue®, with its integrated elasticity, moves with the wood, avoiding joint failure or wood damage. Tentacle Glue's® memory assists the return of joints to their original shape. *Note: Typical white glue, polyurethanes and epoxies are very brittle, stretching only 1-4%. Tentacle Glue® can stretch over 100%!*

Bonds wood, steel, plastics and more: Tentacle Glue® can bond to most substrates including metals, ceramics, rubber, masonry, glass, PVC, ABS, polyurethanes and fiberglass.
Note: Wood Glue bonds only to wood.

Strong, Gap-Filled Bonds: Tentacle Glue's® inherently high tensile strength is ideal for repairs such as chair legs or backs, looks mortises, or joints that have developed gaps. *Note: Most white or polyurethane glues have little or no tensile strength, so can't gap-fill. Compare technical data on our website with other glue websites. Most provide little data, relying on testimonials.*

Exterior Waterproof Tentacle Glue® is Waterproof and Exterior rated. It can also be applied to wet or dry substrates. *Note: most woodworking glues are "water resistant" not "waterproof", cannot be applied or maintain bonds in wet or exterior environments.*

Non-Sag formula Tentacle Glue® is made "to stay where you put it". This highly thixotropic (non-sag) formula resists sagging during application and curing. A 1/4" diameter bead of glue, applied horizontally on a vertical surface, will not run, but will cure in place. This means that it will also stay in place when applied to your project.

Sandable, Paintable Tentacle Glue® is easily sanded and painted! The less-hard nature of this formula makes working it with a sander, chisel or saw very enjoyable. Typical hard epoxies/adhesives tend to be

brittle and can negatively affect a sharp tool edge. This epoxy offers strong, resilient bonds, but is soft enough to shape! Paint or dye this product to match your joint. Use RIT dye from fabric stores @ less than 5% by volume to color the epoxy as needed. Paints and marker stick well for touch-up.

APPLICATIONS: All exterior woodwork including Gates, Doors, Furniture, Trim, Marine, Hot-Tub. Interior applications including chairs, furniture, odd-angled joints, wood-metal or plastic, veneer (like bonding wood veneer to a PVC pipe for a hollow post), attachments like corner details that have small surface area to attach, but must be able to take shock, knot filling, Wooden Boat mfg & repair, Wooden aircraft, model boats.

A handwritten signature in cursive script that reads "Art Quinn". The signature is written in black ink and is positioned to the left of a vertical line.

Art Quinn
President
Advanced Adhesion Inc.